

TECHNICAL DATA

SUPPLY VOLTAGE :	230 VAC 50 / 60 Hz	SIGN DIMENSIONS :	351 x 117 x 78.3 mm
AMBIENT TEMPERATURE (ta) :	0 °C ... +40 °C	VIEWING DISTANCE :	20 m
RATED DURATION :	3 h	PROTECTION CLASS :	IP 65
BATTERY CHARGING TIME :	24 h	INSULATION CLASS :	I
BATTERY TYPE :	3,6 V Ni-Cd		
WATTAGE :	3 W		



- Indoor and Outdoor use
- Moisture Proof
- Single Sided Legend
- Injection-molded thermoplastic ABS housing
- SMD LED application
- High-temperature Ni-Cd battery cells
- Overcharge and deep discharge protection
- 3 hours duration in case of emergency
- Suitable for Damp Locations
- CSA C22.2 No. 141-15 performance certified
- UL-94V-0 flame rating, fire-resistant.
- UL 924 Listed
- Meets NFPA 101 Life Safety Code, NEC, OSHA
- CSA C22.2 No. 141-15 performance certified
- EN 60598-2-22
- Operating Mode: Maintained
- Wall Surface Mounted
- Viewing Distance - 20m
- Packing: 445 x 370 x 270mm
- Master Carton: 12pcs / carton
- Gross Weight: 7.60 kg

